

3732 SERIES - ELECTRONIC DIGITAL MICROMETERS WITHOUT OUTPUT



- Instant inch/mm conversion.
- Zero the reading at any position.
- Starrett no-glare satin chrome finish on thimble and sleeve.
- Balanced, tapered frame for comfortable and accurate measuring.
- Micro-lapped carbide measuring faces.
- Auto OFF after 30 minutes of non-use.
- Extremely hard and stable one piece spindle, the heart of our accuracy and smooth operating one piece friction thimble.
- MEXFL - Thimble with mm scale.
- XFL - Thimble with imperial scale.
- Without data output.
- Sets available.

Cat No	Range	Graduation
3732MEXFL-25	0 - 25mm / 0 - 1"	0.001mm / 0.00005"
3732MEXFL-50	25 - 50mm / 1 - 2"	
3732MEXFL-75	50 - 75mm / 2 - 3"	
3732MEXFL-100	75 - 100mm / 3 - 4"	
3732MEXFL-125	100 - 125mm / 4 - 5"	
3732MEXFL-150	125 - 150mm / 5 - 6"	
3732XFL-1	0 - 1" / 0 - 25mm	0.00005" / 0.001mm
3732XFL-2	1 - 2" / 25 - 50mm	
3732XFL-3	2 - 3" / 50 - 75mm	
3732XFL-4	3 - 4" / 75 - 100mm	
3732XFL-5	4 - 5" / 100 - 125mm	
3732XFL-6	5 - 6" / 125 - 150mm	
S3732BXFLZ	0 - 4" / 0 - 100mm	0.00005" / 0.001mm
S3732CXFLZ	0 - 6" / 0 - 150mm	

795 / 796 SERIES - IP67 ELECTRONIC DIGITAL MICROMETERS



795MEXFL-25

- IP67 level of protection against coolant, water, dust and dirt.
- Instant inch/mm conversion.
- Zero the reading at any position.
- Starrett no-glare satin chrome finish on thimble and sleeve.
- Balanced, tapered frame for comfortable and accurate measuring.
- Micro-lapped carbide measuring faces.
- Extremely hard and stable one piece spindle, the heart of our accuracy and smooth operating one piece friction thimble.
- MEXFL - Thimble with mm scale.
- XRL - Thimble with imperial scale.
- 795 - With data output.
- 796 - Without data output.

Cat No	Range	Graduation
795MEXFL-25	0 - 25mm / 0 - 1"	0.001mm / 0.00005"
795MEXRL-50	25 - 50mm / 1 - 2"	
795MEXRL-75	50 - 75mm / 2 - 3"	
795MEXRL-100	75 - 100mm / 3 - 4"	
795XRL-1	0 - 1" / 0 - 25mm	
795XRL-2	1 - 2" / 25 - 50mm	0.00005" / 0.001mm
795XRL-3	2 - 3" / 50 - 75mm	
795XRL-4	3 - 4" / 75 - 100mm	
796MEXFL-25	0 - 25mm	0.001mm
796XRL-1	0 - 1"	0.00005"
796XRL-2	1 - 2"	
796XRL-3	2 - 3"	
796XRL-4	3 - 4"	

444 SERIES - OUTSIDE MICROMETERS WITH THERMAL INSULATED COVER

- Carbide measuring faces.
- Starrett satin chrome finish - no glare and rust resistant.
- Extremely hard and stable one piece spindle (the heart of our accuracy).
- Ring-type knurled lock nut for quick and sure locking.

Cat No	Range	Graduation
444MXRL-25	0 - 25mm	0.01mm
444MXRL-50	25 - 50mm	
444MXRL-75	50 - 75mm	
444MXRL-100	75 - 100mm	



444MXRL-25