

Digital indicators

S_Dial S229

TECHNICAL SPECIFICATIONS

	905.1201	905.1205	905.1301	905.1303	905.1305	905.5302
Measur. range mm	12.5	12.5	12.5	12.5	12.5	12.5
Version	S229	S229	S229	S229	S229	INT / EXT
Execution ²⁾	S	P	S	S	P	S
Resolution mm	0.01	0.01	0.001	0.001	0.001	0.001
Max. Error fe μm	10 ¹⁾	10 ¹⁾	5	3	5	5
Repetability μm	2	2	2	2	2	2
A mm	66	78.5	66	66	78.5	66
B mm	54	60	54	54	60	54
C mm	50.5	50.5	50.5	50.5	50.5	50.5

	905.1401	905.1405	905.1501	905.1505
Measur. range mm	25	25	25	25
Version	S229	S229	S229	S229
Execution ²⁾	S	P	S	P
Resolution mm	0.01	0.01	0.001	0.001
Max. Error fe mm	10 ¹⁾	10 ¹⁾	5	5
Repetability μm	2	2	2	2
A mm	82.5	102.5	82.5	102.5
B mm	64	83.5	64	83.5
C mm	53.9	53.9	53.9	53.9

	905.1601	905.1621	905.1641	905.1661	905.1671	905.1681
Measur. range mm	50	50	100	100	150	150
Version	S229	S229	S229	S229	S229	S229
Execution ²⁾	S	S	S	S	S	S
Resolution mm	0.01	0.001	0.01	0.001	0.01	0.001
Max. Error fe μm	20 ¹⁾	7	20 ¹⁾	8	20 ¹⁾	9
Repeatability μm	2	2	2	2	2	2
A mm	142.5	142.5	244.5	244.5	351.5	351.5
B mm	121	121	172	172	223	223
C mm	88	88	139	139	194	194

¹⁾ ± 1 digit

²⁾ S = Standard P = Protected