



Stainless Steel Hole Saws

Ideal for cutting stainless and high alloy steels, non ferrous light metals and reinforced fabrics, at a much faster speed than is possible with a bi metal hole saw.

The tough tungsten carbide tipped teeth have a positive cutting angle which provides fast and efficient removal of chips and swarf, cutting depth is 13mm.

Stainless Steel Hole Saws Excellent Cutting Performance



Metal
Inox (Stainless)



Non Ferrous Materials

Advantages:

- Ideal for production cutting, and particularly suitable for use in drills with limited speed control.
- Tungsten carbide tipped teeth provide superb product life and cutting performance.
- Replacement pilot drills are available.
- Complete assembly - there is no requirement to purchase a separate arbor and pilot drill.
- Safety stop at the base of the hole saw prevents drilling beyond maximum cutting depth.
- Cutting depth 13mm (1/2").

SAW SPECIFICATIONS								
DIAMETER		CAT NO	DIAMETER		CAT NO	DIAMETER		CAT NO
MM	INCH		MM	INCH		MM	INCH	
15	19/32"	SM15	28	1.3/32"	SM28	45	1.25/32"	SM45
16	5/8"	SM16	29	1.1/8"	SM29	50	1.31/32"	SM50
17	11/16"	SM17	30	1.3/16"	SM30	51	2	SM51
18	23/32"	SM18	31	1.7/32"	SM31	55	2.5/32"	SM55
19	3/4"	SM19	32	1.1/4"	SM32	60	2.3/8"	SM60
20	25/32"	SM20	33	1.5/16"	SM33	65	2.9/16"	SM65
21	13/16"	SM21	34	1.11/32"	SM34	70	2.3/4"	SM70
22	7/8"	SM22	35	1.3/8"	SM35	75	2.15/16"	SM75
23	29/32"	SM23	36	1.13/32"	SM36	80	3.5/32"	SM80
24	15/16"	SM24	37	1.7/16"	SM37	85	3.11/32"	SM85
25	1"	SM25	38	1.1/2"	SM38	90	3.17/32"	SM90
26	1.1/32"	SM26	39	1.17/32"	SM39	95	3.3/4"	SM95
27	1.1/16"	SM27	40	1.9/16"	SM40	100	3.15/16"	SM100



Tungsten Carbide Tipped Hole Saws

CT Hole Saws offer a cost effective solution for cutting nail embedded wood, or virtually any wood and metal combination, reinforced concrete and fibreglass. This saw is particularly suitable where there is a requirement for a high quality surface finish on the entry and exit hole and it also provides a smooth cut when cutting traditional lathe and plaster.

Advantages:

- Carbide tipped teeth for outstanding cutting performance and product durability.
- Will cut nail embedded wood or virtually any wood and metal combination.
- The perfect choice in applications where quality of entry **and** exit hole is important.
- Suitable for use in mains and battery powered tools.
- Cutting depth 41mm (1 5/8").

SAW SPECIFICATIONS					
DIAMETER		CAT NO	DIAMETER		CAT NO
MM	INCH		MM	INCH	
19	3/4	CT034	76	3	CT300
22	7/8	CT078	79	3.1/8	CT318
25	1	CT100	83	3.1/4	CT314
29	1.1/8	CT118	86	3.3/8	CT338
32	1.1/4	CT114	89	3.1/2	CT312
35	1.3/8	CT138	92	3.5/8	CT358
38	1.1/2	CT112	95	3.3/4	CT334
40	1.9/16	CT196	98	3.7/8	CT378
41	1.5/8	CT158	102	4	CT400
44	1.3/4	CT134	105	4.1/8	CT418
48	1.7/8	CT178	108	4.1/4	CT414
51	2	CT200	111	4.3/8	CT438
54	2.1/8	CT218	114	4.1/2	CT412
57	2.1/4	CT214	121	4.3/4	CT434
60	2.3/8	CT238	127	5	CT500
64	2.1/2	CT212	140	5.1/2	CT512
67	2.5/8	CT258	152	6	CT600
70	2.3/4	CT234			

Tungsten Carbide Tipped Hole Saws

Excellent Cutting Performance



Nail Embedded
Wood



Veneer



Fibreglass



Wood



Plastic



Acrylic



Formica



Plaster



Suspended
Floors



Ceramics



Brick and
Masonry